
CORNER AND NONTYPICAL FLYTABLES

Awkward shape. Reduced stability. Not the typical SJP.

Rev 01 Effective 2026-09-01 Review 2027-09-01 Printed copy uncontrolled

PURPOSE

Stop a corner or nontypical table from being flown on the typical cycle. WorkSafeBC and BC Crane Safety call these out as a separate plan.

SCOPE

The crew when the table is a corner, infill, reduced-width, or any table the drawing or the engineer marks nontypical. Do PROVEN-SWP-028 as well. This SWP does not replace it.

This document is the method - the steps. Hazards and residual risk for the same work are in the JHA library. A procedure is not a hazard analysis.

PROCEDURE

01 NAME IT

This table is nontypical - said on the SJP, said in the brief. If nobody can say why, it is not ready.

02 THE SPECIAL PLAN

Engineered handling plan for this table at the lift. Not a note in the margin of the typical drawing. Pick points, sling lengths, COG, extra tag lines, extra holds - as that plan.

03 THEN THE CYCLE

Do PROVEN-SWP-028 on top of that plan. Gate, drop, roll, attach, fly, land. The crane still does not pull the table out.

04 STOP

Anyone treating it as a typical table, any missing pin, any change from the special plan - stop. Rewrite. Do not improvise a corner fly.

RESPONSIBILITIES

THIS PROGRAM

The published method for the work. Stop-work is named in it. It does not own the site.

SUPERVISOR

Confirms the plan, the crew, the zone and the stop criteria. Owns whether the hook moves.

CRANE OPERATOR

Runs only the machine they are competent on, to the chart, after inspection. Stops on an unclear signal or a broken plan.

RIGGER

Selects, inspects and applies the hitch. Does not guess weight, centre of gravity or angle.

SIGNALPERSON

One set of hands on the crane. Holds the zone. STOP means stop.

WORKER

Works to this program and to site rules - whichever is stricter. Uses the three rights. Reports damaged gear.

FORMWORK SUPERVISOR (HOST)

Drops, rolls and lands the table to the manufacturer cycle and the engineered drawing. The crane crew does not lower jacks or invent a cycling sequence.

PRIME CONTRACTOR

Coordinates floors, drawings, inspections and exclusion. Not a spectator. WorkSafeBC names this duty on flytable work.

REQUIRED COMPETENCY

Same as PROVEN-SWP-028

Can say why this table is not typical, and what the special plan changes

EQUIPMENT

PROVEN-SWP-028 equipment

The special handling plan for this table

PROVEN-SJP-002 / FRM-052 marked nontypical

PPE

Hard hat

CSA-grade footwear

High-visibility clothing

Eye protection

Task-rated gloves

Hearing protection where required

Fall protection where the work exposes a fall

PROHIBITED PRACTICES

Flying a corner table on the typical SJP

Guessing sling lengths because the typical table used them

Skipping the extra tag line or spotter the special plan names

EMERGENCY RESPONSE

Same as PROVEN-SWP-028. A nontypical table that starts to spin is a stop, not a recovery with more hoist.

DOCUMENTATION

PROVEN-SJP-002 / FRM-052 marked nontypical

Special handling plan attached

PROVEN-SWP-028 documentation

REFERENCES

Workers Compensation Act s. 21 - known or reasonably foreseeable hazards; instruction and supervision

OHS Regulation (B.C. Reg. 296/97, in force 15 Apr 1998) Part 3 - OHS program, instruction, inspections

OHS Regulation Part 4 s. 4.13 - risk assessment where rescue or evacuation may arise

OHS Regulation Part 8 - PPE; headwear CSA Z94.1-05 or Z94.1-15

OHS Regulation Part 11 - fall protection

OHS Regulation Part 14 - Cranes and Hoists

14.2(5) - CSA Z150-1998, or ASME B30.5-2004, or ASME B30.22-2005 (articulating boom)

14.2(6) - CSA Z248-2004 for tower, hammerhead and self-erecting tower cranes

14.35 pre-use inspection 14.36 load weight 14.42.1 critical lift 14.44 loads over work areas 14.45 unattended loads

14.47-14.49 signals

OHS Regulation Part 15 - Rigging

Manufacturer load chart, manual and configuration limits

Site lift plan, FLHA and site rules where stricter

WorkSafeBC Flytable Safety (Jul 2025) - drop, roll, fly, land. Critical lift.

BC Crane Safety, 14 Aug 2025 - New WorkSafeBC Video: Flytable Lift Safety

OHS Regulation Part 20 - formwork and falsework. Host / prime duty. This procedure does not write the cycling carpentry.

Manufacturer cycle and shop drawing for this table system - at the lift. Pick points only as the drawing names.

LINKS

SJP - CORNER / NONTIPICAL - PROVEN-SJP-002 -> [/safety/sjp/corner-nontypical-flytable](#)

JHA - CORNER AND NONTIPICAL - PROVEN-JHA-012 -> [/safety/jha/corner-nontypical-flytables](#)

WORKSAFEBC - FLYTABLE SAFETY VIDEO ->

<https://www.worksafebc.com/en/resources/health-safety/videos/flytable-safety>

BC CRANE SAFETY - FLYTABLE LIFT SAFETY -> <https://bccranesafety.ca/new-worksafebc-video-flytable-lift-safety/>

EFCO E-Z FLY (OEM PAGE) -> <https://www.efcoforms.com/products/shoring/e-z-fly-tables/>

DOKA DOKATRUSS TABLE (OEM PAGE) ->

https://www.doka.com/us/system-groups/doka-floor-systems/tableforms/dokatrusstable/DokaTruss_table

ALUMA TRUSS (OEM PAGE) -> <https://aluma.com/aluma-truss-table-shoring>